

3 AA BATTERIES

XPP-5418GX/RX-K01

INTRINSICALLY SAFE FLASHLIGHT

NIGHTSTICK[®]
Life Depends on Light[™]

IP-X7
WATER
PROOF



Large, textured button that is
easy-to-use with gloves



Durable polymer body is
impact & chemical resistant



Non-conductive body for
hazardous environments



Sharp focused flashlight beam
for **distance illumination**



AVAILABLE IN MULTIPLE COLORS

XPP-5418RX-K01

200 LUMENS



1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5418GX-K01, UPC 0 17398 80620 6
- XPP-5418RX-K01, UPC 0 17398 80622 0

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, fire and rescue

CERTIFICATIONS

- cETLus, ATEX, IECEX, CE, NFPA, InMetro

CASE MATERIAL

- Engineered polymer

FLASHLIGHT LUMENS/RUNTIME

- 200L, 10.5 hrs. runtime

CANDELA

- 5,129

BEAM DISTANCE

- 143 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.6 in (142 mm)
- HANDLE DIAMETER: 0.75 in x 1.4 in (19 mm x 35 mm)
- HEAD DIAMETER: 1.5 in (38 mm)
- WEIGHT: 5.4 oz (153 g)

POWER SOURCE



- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Multi-angle mount with hardhat slot and brim mounts

FL 1 STANDARD		
		
		

Bayco Products, Inc. XPP-5418GX/RX
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga Ex ia IIC T3 Ga © II 1 G Ex ia op is IIC T3 Ga	Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27837X IECEX ITS 16.0067X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell with three in series Energizer E91 or EN91
--	---

WARNINGS:
 Replace batteries in a non-hazardous location.
 Use only Energizer AA Model E91 or EN91 batteries.

AVERTISSEMENT:
 Remplacer les piles dans une zone non dangereuse.
 Utiliser uniquement les piles Energizer AA - modèle E91 ou EN91.

CE 2575

Segurança

 INMETRO OCP 0034
 Ex ia op is IIC T3 Ga
 -20°C ≤ Tamb ≤ +40°C
 NCC 15.0208 X

CERTIFIED